

PS300



Telemeter Electronic

28V POWER SUPPLY

The PS300 is a solid state hand-portable power supply delivering a maximum of 300 amps at a pre-set voltage of 28V DC for avionics use.

The unit can be connected directly to the aircraft's external ground power receptacle and is primarily for regional airline operators of turbine and turboprop DC aircraft or MROs requiring continuous power for maintenance. It has also been used to power large DC aircraft at various air shows.

The PS300 is compact and lightweight and able to power air conditioning on most business jets. It can be placed under the fuselage or wing of small aircraft or helicopters, freeing up hangar floor space.

The PS300 is fitted with three 100A power supplies connected in parallel. Power supply healthy LEDs are fitted to the front panel for diagnostics. When pressed, the emergency stop button immediately disconnects power to the aircraft.

The front-mounted quick-disconnect output connector allows leads of different configurations to be instantly connected to the unit. Key-switch input voltage selection allows operation at either 180-264V AC three phase or 311-457V AC/47-63Hz three phase for international use. A solid state voltmeter and ammeter displays the output voltage and current, enabling operators to monitor the current draw of avionics and other pre-flight loads. Supplied with Nato lead set, input lead and heavy-duty canvas protective jacket.

Supplied as standard with



Input lead




13ft Nato lead



Padded protective jacket



Typical power plant:*



*This information is given in good faith

PS300

Specifications

Output voltage	28V DC
Output current	300A
Output ripple	<200mV p-p
Input voltage 1	315 –457V AC/47–63Hz three phase + neutral + earth
Input voltage 2	180–264V AC three phase + earth
Input current	16A @ 400V AC; 32A @ 200V AC/three phase (typical)
Operating temp	–20°C to +50°C (–2°F to +122°F)
Case	Aluminium with shock absorbing feet
Voltmeter/Ammeter	Solid state LED, IP65
Aircraft cable	4m (13ft) with Nato plug
Input cable	3m (10ft) with 32A 5 pin 6h red plug
Cooling	Forced ventilation
Protections	Thermal, current overload, short circuit, over voltage
Dimensions	L 450mm (18in) W 295mm (11in) H 345mm (13in)
Weight	20kg (44lb)
NCAGE	KD628

Features

- Input supply on/off switch
- Power supply LED status indicators
- Short circuit/current limit protection
- Emergency stop push-button
- Corrosion resistant aluminium case with carry handles
- Replaceable/washable air filters allows outdoor use
- 4-metre aircraft cable with Nato connector
- Harsh environment input cable with plug
- Solid state voltmeter
- Solid state ammeter
- Fitted with rubber anti-slip, shock absorbent feet
- Heavy-duty canvas protective jacket

Optional extras



Universal single trolley



PS300: in operation on a Dornier 328



Other ground power units available from AERO Specialties

